

E-BAND PRODUCT SPECIFICATIONS

	GE80 Gigabit Ethernet Link	AR80 AdaptRate™ Gigabit Ethernet Link
Data Rate	1000 Mbps full duplex	1000/100 Mbps full duplex
Latency	< 50 microseconds	< 50 microseconds @ 1000 Mbps
		< 150 microseconds @ 100 Mbps
RF Interface	73.5/82.5GHz (FDD), digitally modulated (BFSK) with Forward Error Correction (RS 204,188)	
	1.4GHz bandwidth	1.4GHz bandwidth @ 1000 Mbps
		140MHz bandwidth @ 100 Mbps
AdaptRate Switching Time	Not applicable	< 50 milliseconds
Ethernet Interfaces	1000Base-SX with LC connectors – up to 270 meters 62.5/125µm MMF, or 500 meters 50/125µm MMF	
	10/100Base-TX with RJ-45 connector – up to 100 meters Cat 5 cable (surge protectors required)	
	Up to 1518-byte standard Ethernet frames (1522 bytes with 802.1q VLAN tags)	
	Configurable MAC address learning and RF link state propagation	
Management	Web-based (HTML) embedded management agent: setup, security, status, statistics, software update	
Mount	Fine-adjust pole mount: 6-11 cm (2.5-4.5 in.) OD	
Size	Radio + antenna: 33w * 33h * 22d (cm); with mount: 50w * 36h * 25d (cm)	
Weight	Radio + antenna + mount: 10 kg (22 lbs)	
Environmental	Operating temperature: -30 to +50 °C (-22 to 122 °F)	
	Operating altitude: 4,500 meters (max.)	
Wind Loading	60 lbs force @ 100MPH	
Regulatory	Safety: UL Listed; meets FCC 1.1310 general population RF MPE limits	
	RF Certification: US FCC Part 101	
Install Kit	Voltmeter test cable, power connectors	

AIRLINX Communications, Inc.
 Box 253
 Greenville, NH 03048
 E-mail: sales@airlinx.com
 Tel: (888) 224-6814
 Fax: (603) 878-0530